



**LIFETIME LIMITED WARRANTY**

GutterDome, Inc. (hereinafter referred to as "GDI") warrants for the lifetime of the product to the original owner(s) (hereinafter referred to as "you") (and is automatically transferrable one (1) time to a new owner in the event you no longer own your home or structure) in the event that its specially designed GutterDome gutter guards will not be defective in manufactured parts. GutterDome products are subject to the terms and conditions as set forth below. No other warranty is expressed or implied in this Lifetime Limited Warranty (hereinafter referred to as "Warranty"). This warranty gives you specific legal rights, and you may also have other legal rights, which vary from state to state.

**What Does This Lifetime Limited Warranty Cover?**

This Warranty covers only genuine GutterDome gutter guards. It is the customer's responsibility to verify that the product installed is GutterDome. If a GutterDome gutter guard manufactured part is defective, GDI agrees at its sole discretion, to either repair the defect or replace the defective part with either a new or a reconditioned part that is equivalent. GDI's obligation under this Warranty shall at no time exceed the original purchase price of the product at time of sale.

**What Does This Warranty Not Cover?**

This Warranty does not cover labor charges for replacing, repairing, and installing or re-installing any defective parts. This Warranty does not cover consequential damages (the cost of replacing or repairing other property that is damaged resulting from the defective warranted part) nor does it cover any incidental damages (costs you may incur in order to obtain warranty service, such as telephone charges, time lost from work, etc.).

This Warranty is void if any of the following conditions occur: improper installation; alterations from original installation; panel removal; settlement of building structure; structural shrinkage or distortion of structure (warping of roof or gutter over time); vandalism; salt; hail; fire; tornado, windstorm, earthquakes; lightning; protective liquids of any type of roof preservation product applied to rooftops to extend the life of the roof; tree sapping on mesh; insect/bird droppings on mesh; accidental damage; acts of God; misuse or abuse of the gutter guard; mildew accumulation; paint over spray; moss accumulation; impact of foreign objects; normal weathering; caustic atmospheric conditions; unreasonable uses or failure to provide reasonable maintenance or any other causes beyond the control of GDI.

*NOTE: Icicles may form in extreme temperatures where ice and snow are present.*

**When is The Coverage in Effect?**

This Warranty becomes effective when an Authorized Dealer of GutterDome and you complete the warranty application, (located on the bottom of this Warranty) and mail it to the GDI corporate office within thirty (30) days, after the installation is complete. Failure to do so will render this Warranty null and void.

**How Long Does the Warranty Last?**

GutterDome (GD45; GD45M *Magma*; GD45A *Adjustable*; GD45AM *Adjustable Magma*; GD67; and GD67M *Magma*) Warranty is valid for the lifetime of the product, which is for a period of thirty (30) years and GutterDome (GD45P *uPVC*) Warranty is valid for the lifetime of the product, which is for a period of twenty (20) years, only if the initial installation was performed by an Authorized Dealer of GutterDome. If anyone other than an Authorized Dealer of GutterDome initially installed the parts, the Warranty on GutterDome will then be for a period of five (5) years and is non-transferrable.

**How Do You Get Warranty Service?**

To obtain Warranty service, you must notify GDI, either in person or in writing, before the Warranty period has expired and within a reasonable period of time after discovering the defect. If you choose to notify GDI in writing you must reference the original date of purchase, the original date of installation, the name and contact information of the original person or company that did the installation and your name and contact information.

GDI reserves the right to withdraw this warranty from the market at any time. Any and all warranties in effect at the time of removal will not be affected by the withdrawal and will remain in affect until their expiration.

GDI cannot and will not be liable to you or any subsequent owner(s) for a breach of any written or oral express warranties, such as those given to you by an Authorized Dealer of GutterDome, contractor, sub-contractor or installer of GutterDome gutter guards. Any implied warranties imposed by law, such as the implied warranties of merchantability and fitness for a particular purpose are Limited in time to the duration of this express warranty. GDI shall not be liable for any consequential damages for breach of any express, written, oral or implies warranty on any GutterDome gutter guards. Your exclusive remedy shall be repair or replacement solely at GDI's discretion and only under the terms stated in this Warranty. Some states do not allow the exclusion or limitation of incidental or consequential damages and some states do allow limitations on how long an implied warranty lasts, so the above limitations or exclusions may not apply to you.

ANY REPAIR OF THE PRODUCT UNDERTAKEN WITHOUT PRIOR WRITTEN AUTHORIZATION FROM GDI WILL VOID THIS WARRANTY.

**Application for Lifetime Limited Warranty**

**Customer's Information**

Name: \_\_\_\_\_

Customer's Signature: \_\_\_\_\_

Address: \_\_\_\_\_

City, State, Zip: \_\_\_\_\_

Phone Number: \_\_\_\_\_

Date of Installation: Month \_\_\_\_\_ Day: \_\_\_\_\_ Year: \_\_\_\_\_

**Authorized Dealer's Information**

Name of Installer: \_\_\_\_\_

Installation Company: \_\_\_\_\_

Address: \_\_\_\_\_

City, State, Zip: \_\_\_\_\_

Phone Number: \_\_\_\_\_

**Mail the completed Application for Lifetime Limited Warranty to the following:**

GutterDome, Inc., P. O. Box 1786, Lincoln, California 95648-1446

Toll Free: 877-987-4888

**White Copy** = GutterDome, Inc.

**Yellow Copy** = Authorized Dealer

**Pink Copy** = Customer



## Product Care and Maintenance

GutterDome is the finest micro-mesh gutter guard in North America that is available for professional installation. GutterDome recommends that the following care and maintenance procedures be adhered to in order to get the maximum lifetime out of your “Award Winning” GutterDome gutter protection system.

Gutters must be thoroughly cleaned and downspouts as well as underground drains must be cleared of any existing debris or obstructions. Gutters may need to properly sloped, aligned and pitched and all screens must be removed prior to installation.

Product requires virtually no maintenance and in most cases, rainfall alone is sufficient to keep it clean. However, there may be some instances where cleaning/maintenance will be required. Light winds should remove most surface debris (*due to the guards patented dome design*), but if debris is wet or compressed, higher and stronger winds may be required to properly effect shedding.

To ensure maximum performance, it may be necessary to spray off the product with an ordinary garden or pressure hose from the safety and security of the ground. This will help prevent silt type buildup and residue. Utilizing the Dealer offered (*for sale*) cleaning brush and pole from the safety and security of the ground is ideal to augment this effort. A mild surfactant or degreaser (*must not contain any harsh additives or chemicals*) may be used during this maintenance.

In certain geographic locations where cottonwood trees, hardwood tassels, excessive tree sap and/or resins from trees are prevalent, it may be necessary to spray off the product more frequently to prevent build-up and minor runoff. Geographic location, the quality of the atmosphere and other local factors over which GutterDome has no control, may contribute to the severity of these conditions.

Mildew or mold can collect on all types of building products if not cared for correctly. These conditions can be eradicated by utilizing a cleaning solution during the aforementioned maintenance process. Rinse thoroughly after use and do not exceed the recommended concentration of the cleaners. To do so may cause irreparable damage to the product. Always follow manufacturer’s instructions of their cleaning compounds.

Caulking compounds, tar and similar substances can leach from some roofing materials and mesh clogging may occur. In addition, animal droppings may be present on top of the stainless steel wire mesh. To remove these substances, use reasonable amounts of mineral spirits applied directly to the foreign substance. Test in an inconspicuous area first to ensure product finish is not compromised. Painting of the product and over the clear anodized coating will void the warranty.

Organic debris may buildup on top of an inside valley corner, if this does happen, simply brush off the excess debris with the Dealer offered (*for sale*) cleaning brush and pole from the safety and security of the ground. Secondary runoff may be experienced at the termination of long or steep valleys or if excess debris is not removed.

During a rain storm, water may be seen dripping off the lip of the product. This is not due to the malfunction of the product. Similar to your rain gutter system, product has a drip edge on the front that sits over the lip of the gutter to assist in the shedding of debris. Common for rain water to gather at this location and gently drip off the front lip of the gutter system and fall to the ground below.

Gutter guards may assist in reducing the amount of ice build-up in your rain gutter system that impedes the freeze/thaw process that naturally occurs during extremely cold weather conditions. Ice in gutters often causes seams to split, hangers to loosen and gutters to pull away from the main building structure. GutterDome does not promote that the system will limit or prevent ice damming, which is caused by inadequate insulation and poor roof ventilation. Icicles are a law of nature that may occur during the cold Winter months and are an indication the gutter guards are protecting the investment in your rain gutter system and not indicative of product performance failure.